

# ADBLUE<sup>®</sup> COMBI

## A flexible and modular solution

- > Lane orientation
- > ATEX version available
- > Coriolis meter
- > AdBlue<sup>®</sup> with up to 3 petrol/diesel grades
- > Easy hose handling



# Product specifications

The SK700-II AdBlue<sup>®</sup> is one of the many modular designs available with the SK700-II series, so it fits seamlessly with the rest of the systems and solutions on your forecourt. Combined with up to three petrol/diesel grades the SK700-II AdBlue<sup>®</sup> Combi provides flexibility and reliability whatever your forecourt requirements.

## Technical Specifications & Standard Features

Hydraulics	Stainless steel Coriolis meter AdBlue   Stainless steel internal piping and connections   Petrol/Diesel delivery – suction or pressure   AdBlue delivery – Pressure   Non return valve and filter   AdBlue flow rate: 4L - 40L per minute   Power supply: 230V (+10% -15%), 50Hz ± 2Hz
Electronics	Calculator Gilbarco Sandpiper-II   LCD display (backlit)   Interface: 2-wire, IFSF-LON, ATCL, PUMA LAN
Mechanical	<b>Electronics</b> – Stainless steel valves   <b>Housing</b> – Powder coated steel   <b>Hose</b> – 3.3m, black   <b>Hose management</b> – Internal hose with retraction as standard   <b>Nozzles</b> – ZVA
Options	Elaflex swivel   Electromechanical totalisers   Nozzle adaptor   AdBlue preset available   AdBlue specific hose   Stainless steel hose column   Stainless steel installation kit   Stainless steel hydraulic top cover   Enhanced corrosion protection   SK700-II standard options

Versions	Standard	Heated Hose	Heated Hose ATEX
Hydraulic cabinet heater	Fuheat system	Fuheat system	Trace heater around hydraulics
Hose column heater	Fuheat system	Hose with trace heater	Hose with trace heater
Power consumption	950 watts	700 watts	450 watts
Min. operating temperature	up to -40°C	up to -40°C	up to -25°C
Compartment isolation	Standard up to -25°C   Optional up to -40°C	Standard up to -25°C   Optional up to -40°C	for up to -40°C
AdBlue breakaway	Available	Available up to -25°C	Available up to -25°C
Nozzle cover	Protective nozzle door	Simple nozzle cover needed only for < -25°C	Simple nozzle cover always needed for ATEX
Certifications	MID	MID	MID & ATEX

Isolation needed for temperature < -25°C for all models. ATEX available only up to -25°C

